

TWN4 MULTITECH CORE

PROGRAMMABLE RFID READER/WRITER MODULE FOR LF/HF/NFC WITHOUT ANTENNA



Version C0



Version C1



Version C2

Elatec's TWN4 family of transponder readers and writers allows users to read and write to almost any 125 kHz, 134.2 kHz and 13.56 MHz tags and/or labels – it supports all major transponders from various suppliers like ATMEL, EM, ST, NXP, TI, HID, LEGIC, etc. and ISO standards like ISO14443A/B (T=CL), ISO15693, ISO18092 / ECMA-340 (NFC).

The TWN4 MultiTech Core is designed for integration into machines or any other device to be used with an external antenna (125 kHz/134.2 kHz, 13.56 MHz or both).

Special features:

- + powerful SDK for writing apps which are executed directly on the reader
- + firmware update in the field possible
- + onboard 18 kB flash storage, e.g. for storing user accessible non-volatile data
- + direct chip-commands support
- + supports connection of external ISO7816 compatible SAM cards
- + supports 50 Ohm external antennas via SMA, SMB, SMC, MCX, UMCC/U.FL connectors
- + CCID and PC/SC 2.01
- + dedicated expansion bus for connection of LCD, mass storage, etc.
- + supports quick (re)configuration over network and over wireless interface with TWN4 CONFIG Card
- + TWN4 Upgrade Card for P and PI options available on request
- + 3D construction data (STEP) available on request



Elevator



EV Chargers



Access



Shop POS



Fitness
Equipment



Ticket POS



PC Log-on



Document
Management



Driver ID



Vending



Parking



Gaming



Locker Locks



Time
Attendance



Industrial
PC

TECHNICAL DATA

FREQUENCY	125 kHz/134.2 kHz (LF) / 13.56 MHz (HF)								
ANTENNA	Externally, 50 Ohm for 13.56 MHz – 490 μ H \pm 5% for 125 kHz/134.2 kHz								
DIMENSIONS (L X W X H)	C0 Version: 39 mm x 30 mm x 4.6 mm / 1.54 inch x 1.18 inch x 0.18 inch C1 Version: 39 mm x 30 mm x 8 mm / 1.54 inch x 1.18 inch x 0.31 inch C2 Version: 39 mm x 30 mm x 9 mm / 1.54 inch x 1.18 inch x 0.35 inch								
POWER SUPPLY	3.3 V +/- 5% or (by using onboard voltage regulator) 4.3 V - 5.5 V								
CURRENT CONSUMPTION	RF field on: 120 mA typically / Sleep: 500 μ A typ. / Cyclic Operation: TBD								
TEMPERATURE RANGE	Operating: -25 °C up to +80 °C (-13 °F up to +176 °F) Storage: -45 °C up to +85 °C (-49 °F up to +185 °F)								
RELATIVE HUMIDITY	5% to 95% non-condensing								
READ- / WRITE DISTANCE	Up to 100 mm / 4 inch, depending on antenna, environment and transponder								
TRANSMISSION SPEED	Host: USB Full speed (12 Mbit/s), RS-232: up to 115.200 baud; Air: up to 848 kbit/s								
OPERATING MODES (USB)	USB keyboard emulation – USB virtual COM port – CCID / PC/SC 2.01								
MTBF	500,000 hours								
WEIGHT	Approx. 7 g								
SUPPORTED TRANSPONDERS (STANDARD)	<p><u>ISO14443A:</u> LEGIC Advant¹⁾, MIFARE Classic EV1²⁾, MIFARE Classic, MIFARE Mini, MIFARE DESFire EV1, MIFARE DESFire EV2²⁾, MIFARE Plus S, X, MIFARE Pro X³⁾, MIFARE Smart MX³⁾, MIFARE Ultralight, MIFARE Ultralight C, MIFARE Ultralight EV1, NTAG2xx, PayPass³⁾, SLE44R35, SLE66Rxx (my-d move)³⁾, Topaz</p> <p><u>ISO14443B:</u> Calypso³⁾, Calypso Innovatron protocol³⁾, CEPAS³⁾, HID iCLASS¹⁾, Moneo³⁾, Pico Pass⁴⁾, SRI4K, SRIX4K, SRI512, SRT512</p> <p><u>ISO18092 ECMA-340:</u> NFC Forum Tag 1-5, NFC Peer-to-Peer, Sony FeliCa⁵⁾, NFC Active and passive communication mode</p> <p><u>ISO15693:</u> EM4x33³⁾, EM4x35³⁾, HID iCLASS¹⁾, HID iCLASS SE/SR¹⁾, ICODE SLI, LEGIC Advant¹⁾, M24LR16/64, SRF55Vxx (my-d vicinity)³⁾, Tag-it, PicoPass⁴⁾</p> <p><u>125 kHz, 134.2 kHz:</u> AWID, Cardax, CASI-RUSCO, Deister⁶⁾, EM4100, 4102, 4200⁷⁾, EM4050, 4150, 4450, 4550, EM4305⁸⁾, FDX-B, EM4105, HITAG 1⁹⁾, HITAG 2⁹⁾, HITAG S⁹⁾, ICT⁸⁾, IDTECK, Isonas⁸⁾, Keri, Miro, Nedap⁶⁾, PAC, Pyramid, Q5, T5557, T5567, T5577, TIRIS/HDX, TITAN (EM4050), UNIQUE, ZODIAC</p>								
SUPPORTED TRANSPONDERS (VERSION P)	All Standard Transponders, Cotag, G-Prox ⁶⁾ , HID DuoProx II, HID ISO Prox II, HID Micro Prox, HID ProxKey III, HID Prox, HID Prox II, Indala, ioProx, Nexwatch								
SUPPORTED TRANSPONDERS (VERSION PI)	Requires external TWN4 SIO Card, All Standard Transponders, All Version P Transponders, HID iCLASS ¹⁰⁾ , HID iCLASS SE/SR/SEOS(CSN and Facility Code/PAC) ¹⁰⁾ , HID iCLASS Elite & SE Elite								
OS SUPPORT	Windows XP, Vista, Embedded CE ⁸⁾ , 7 (32-/64-bit), 8, 8.1, 10, Linux, Android ⁸⁾ , iOS ⁸⁾ , MAC OS X ⁸⁾								
PERIPHERAL INTERFACES	USB, RS232, 2 x serial (logic level 3.3 V, CMOS 5 V tolerant), I ² C, SPI, 8 GPIOs, CAN ⁸⁾ , Clock/Data, Wiegand, 1-Wire ⁸⁾								
CERTIFICATION NAME	TWN4 MIFARE NFC								
CERTIFICATION(S)	RoHS-II compliant								
ORDER CODE(S)	<table> <tr> <td>T4CM-FC0</td> <td>C0 Standard</td> </tr> <tr> <td>T4CM-FC0-P</td> <td>C0 Version P</td> </tr> <tr> <td>T4CM-FC0-PI</td> <td>C0 Version PI</td> </tr> <tr> <td>T4CM-FC1</td> <td>C1 Standard</td> </tr> </table>	T4CM-FC0	C0 Standard	T4CM-FC0-P	C0 Version P	T4CM-FC0-PI	C0 Version PI	T4CM-FC1	C1 Standard
T4CM-FC0	C0 Standard								
T4CM-FC0-P	C0 Version P								
T4CM-FC0-PI	C0 Version PI								
T4CM-FC1	C1 Standard								

